

YETDA INDUSTRY LTD.

1.5" 16*16 RED DOT MATRIX DISPLAY

M-1516162AUF21-JY

DESCRIPTION

*1.5" (38.1mm) Inch Matrix Height.

* Super Bright Red Dot Matrix.

* Grey Face and White Dot Color.

* Row Common Anode.

ABSOLUT MAXIMUM RATINGS AT Ta=25°C

Parameter		UNIT
Power Dissipation Per Dot	40	mW
Peak Forward Current Per Dot	120	mA
Forward current Per Dot (Static)	30	mA
Reverse Voltage Per Dot	5	V
Operation Temperature Range	-25°C TO +80°C	°C
Storage Temperature Range	-25°C TO +100°C	°C
Lead Soldering Temperature	260°C for 3 seconds 1.6mm(1/16 inch) from body	

ELECTRICAL/OPTOTICAL CHARACTERISTIC AT Ta=25°C


PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITION
Average Luminous Intensity	I _v	50	60		mcd	If=20mA
Peak Emission Wavelength	λ d		625		nm	If=20mA
Forward Voltage Per Dot	V _f		2.0	2.4	V	If=20mA
Reverse Current Per Dot	I _r			10	uA	V _r =5V
Luminous Intensity Matching Ratio	I _{v-m}	2 : 1				If=20mA



YETDA INDUSTRY LTD.

P.C.B. Pin Connection


COL	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
ROW	1	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
2	○	○	○	○	+											
3	○	○	○	○	+											
4	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	25
5	○	○	○	○	+	+	+	32	+	+	+	+	+	+	+	
6	○	○	○	○	+											
7	○	○	○	○	+											
8	○	○	○	8	+									24	+	
9	○	○	○	○												
10	○	○	○	○												+
11	○	○	○	○												+
12	9	+	+	+	+	+	+	+	16	+						
13	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
14	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
15	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	+
16	○	○	○	○	○	○	○	○	○	○	○	○	○	17	+	





YETDA INDUSTRY LTD.

Reflector Dimensions



Unit:mm